



AT-300
ATEX



	1530x1190x2330 mm.
	370 Kg.

AT-500
ATEX



	2150x1190x2330 mm.
	525 Kg.

AT-750
ATEX



	2800x1190x2330 mm.
	730 Kg.

AT-1000
ATEX



	3470x1190x2330 mm.
	835 Kg.



ASPIRADOR INDUSTRIAL
CON NORMATIVA ATEX

INDUSTRIAL DUST COLLECTOR
WITH ATEX DIRECTIVE

ASPIRATEUR INDUSTRIELLE
AVEC DIRECTIVE ATEX



Filtro limpieza neumático
Pneumatic cleaning cartridge filter
Filtre nettoyage pneumatique



Deposito de recogida Collector deposit Dépôt de collecte

	AT-300	AT-500	AT-750	AT-1000
Potencia motor Motor power Puissance moteur	3 Hp. (Tri.380V)	5 Hp. (Tri.380V)	7,5 Hp.(Tri.380V)	10 Hp. (Tri.380V)
Caudal aspirable Air speed Débit d'aspiration	2.310 m ³ /h	3.525 m ³ /h	5.185 m ³ /h	7.745 m ³ /h
Presion estatica Static pressure Pression estatique	10 inch/h2o	11,2 inch/h2o	10 inch/h2o	11 inch/h2o
Superficie de filtrado Filter surface Surface de filtrage	10 m ²	20 m ²	30 m ²	40 m ²
Ø Boca de aspiración Dust inlet Ø Ø Buses d'aspiration	150 mm.	200 mm.	250 mm.	300 mm.
Nivel sonoro Noise level Niveau sonore	70 db.	73 db.	77 db.	80 db.



Respiradero anti-explosión ATEX
Anti-explosion vent ATEX
Ventiler antidéflagrant ATEX